

INTRODUCING NEW! SUPER PAINTGUARD™

New Super PaintGuard™ collection media from the Cumulus Fibres line provides superior paint holding capacity while limiting runoff compared to the leading premium collection media. Super PaintGuard™ rivals the efficiency seen in higher priced collection media.



Our patented dual-stage construction allows the more porous first layer to collect the overspray; meanwhile, the engineered high efficiency of the final layer holds more paint in the filter preventing it from entering a down stream air system.



The inline one-piece design provides higher strength in fully loaded capacity. Replace your higher priced premium collection media today with Cumulus Fibres' newly designed Super PaintGuard™.



Paint Spray Method
4F342 @ 40 PSI Speedaire

Spray Feed Rate
136 Gms/Min

Air Velocity
150 FPM

Product	Paint Hold Capacity Gms.	Paint Run-Off Gms.	Penetration Gms.	Efficiency %	Initial Resistance
Super PaintGuard™	2628.0	269.6	19.7	99.33	.03 w g
Brand X	2422.2	489.9	19.1	99.35	.05 w g



a division of Polyester Fibres
1101 Tarheel Road · Charlotte, North Carolina 28613
Phone: 704.394.2111 · Fax: 704.394.2650

For more information please visit us at www.poly-fibers.com.